Datasheet

Horn Speaker

Horn Speaker (Short)

Alta Horn Speakers

Deter threats early with a visible speaker



Strengthen your Alta Protect system with the Avigilon Alta Horn Speaker. Go beyond deterrence with live voice warnings and powerful talk-down capabilities to help stop threats in real time. Connect directly to the cloud or integrate seamlessly as an ONVIF-conformant speaker.



Compliant with NDAA 2019 Section 889

Two-way audio deterrence



Engage in real-time communication with live talk-down capabilities to deter threats and take control of security events as they happen.



Quick & easy installation

Designed for fast deployment with minimal wiring and hardware requirements, the Alta Horn Speaker can be up and running in just a few minutes.





Intuitive setup process with user-friendly tools makes it easy to configure the Alta Horn Speaker settings for your unique environment.



Advanced audio capabilities

Detect, classify and respond to sound events with built-in analytics that enhance situational awareness and automation.

Remote control & management



Access, manage and control speaker functions from anywhere via the cloud—perfect for multi-site security operations.

Weather-resistant



Built to withstand tough outdoor conditions, the Alta Horn Speaker is rated for durability in harsh environments, ensuring consistent performance year-round.

To learn more, visit https://www.avigilon.com/alta-protect/horn-speaker



1

Specifications

Connectivity	
Ethernet	802.3u 10/100 Ethernet
Network protocols	IPv4, SIP, NTP, TCP, UDP, HTTP, HTTPS, ONVIF
Security	
Security	Trusted Platform Module (TPM 2.0) Factory-installed certificates No default passwords Mandatory access authentication HTTPS/TLS encryption
Audio	
Speaker features	Talk down Alarm
Peak SPL (Horn Speaker)	119 dB with PoE 123 dB with PoE+
Peak SPL (Short Horn Speaker)	115 dB with PoE 119 dB with PoE+
Frequency range (Horn Speaker)	290-7000 Hz
Frequency range (Short Horn Speaker)	350-7000 Hz
Dispersion (-6dB) 1kHz/4kHz (Horn Speaker)	81°/37°
Dispersion (-6dB) 1kHz/4kHz (Short Horn Speaker)	140°/33°
Microphone features	Audio classification Recording Two way (half duplex) talk-down
Microphone configuration	1x microphones



Environmental		
Temperature (operating)	-30°C to +50°C (-22°F to 122°F)	
Temperature (storage)	-40°C to +60°C (-40°F to 140°F)	
IP rating	IP66 IP67	
Power		
Power source	PoE 802.3at PoE+ 802.3af	
Power consumption (max.)	25W	
Power consumption (typical)	5W	
Mechanical		
Material/Color	ASA / RAL7035 Light grey	
Mounting	Bracket	
Adjustment range	Tilt	
Dimensions	Horn Speaker: 202 x 273 x 347 mm (7.93 x 10.75 x 13.68 in) Short Horn Speaker: 145 x 200 x 208 mm (5.71 x 7.85 x 8.21 in)	
Weight	Horn Speaker: 2.1 kg / 4.62 lb Short Horn Speaker: 1.7 kg / 3.75 lb	
Packaging dimensions	Horn Speaker: 280 x 208 x 368 mm (11 x 8.18 x 14.48 in) Short Horn Speaker: 222 x 212 x 212 mm (8.74 x 8.34 x 8.34 in)	
Packaging weight	Horn Speaker: 2.4 kg (5.29 lb) Short Horn Speaker: 2.0 kg (4.40 lb)	
In the box	Device Wall Bracket Screws for Pole and Corner mount (PLMT-1001/CRNMT-1001)	



Compliance	
EMC	FCC: FCC Part 15 Subpart B Class B IC: ICES-003 issue 7 CE: EN 55032 Class B, EN55035:2017/CISPR 35
Safety	UL: CAN/CSA 62368-1, ANSI/UL 62368-1 CB: IEC62368-1
Warranty	
Warranty	10 years (requires a valid license)

Analytics specifications


Supported audio events	
Audio Events	 Glass breaking Loud noise Gun shot Screaming Smoke alarm Car alarm Ultrasound panic alarm Dog bark Tire screeching




Outline Dimensions


Alta Horn Speaker

















Alta Short Horn Speaker
















Ordering Information

Product ID	Description
220-4511A	IP Horn speaker (HORNSPEAKER)
220-4515A	Short IP Horn speaker (HORNSPEAKER-S)

Accessories

Product ID	Description
PLMT-1001	Pole Mounting Bracket
CRNMT-1001	Corner Mounting Bracket

Applicable licenses

Product ID	Description
AUD-CLD-1Y	1 year license per audio device connected to Alta Cloud.
AUD-CLD-3Y	3 year license per audio device connected to Alta Cloud.
AUD-CLD-5Y	5 year license per audio device connected to Alta Cloud.
AUD-CLD-10Y	10 year license per audio device connected to Alta Cloud.

Note: These audio licenses are specifically for audio-only devices connected to Alta Cloud, and are not required for Alta cameras that feature in-built audio capabilities or that have line-in or line-out ports included.



Support

For product support, visit: avigilon.com/support or to contact Sales, email sales@avigilon.com.

To learn more, visit: avigilon.com/alta-protect/horn-speaker, or to read the customer documentation, see docs.avigilon.com/bundle/alta-video/page/Products/Hornspeakers.htm.

Oct 2025 | Rev 0 Draft 5



